

AD-A047 051

HUGHES AIRCRAFT CO FULLERTON CALIF GROUND SYSTEMS GROUP
FLOATING DECK GRID MODULATOR.(U)
NOV 77 D V SAVAGE

F/G 9/5

UNCLASSIFIED

ECOM-77-2647-1

DAAB07-77-C-2647

NL

| OF |
AD
A047051



END
DATE
FILMED

12-77

DDC



12
B.S.

11

AD

AD A O 47051

Research and Development Technical Report
ECOM-77-2647-1

FLOATING DECK GRID MODULATOR

D. V. SAVAGE
HUGHES AIRCRAFT COMPANY
GROUND SYSTEM GROUP
FULLERTON, CA 92634

November 1977

First Interim Report for Period March 1977 to June 1977


DISTRIBUTION STATEMENT
APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

AD No. _____
DDC FILE COPY

Prepared for

ECOM

US ARMY ELECTRONICS COMMAND FORT MONMOUTH, NEW JERSEY 07703



NOTICES

Disclaimers

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The citation of trade names and names of manufacturers in this report is not to be construed as official Government indorsement or approval of commercial products or services referenced herein.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator.

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM
1. RESEARCH NUMBER (18) ECOM 77-2647-1	2. GOVT ACCESSION NO.	3. RECIPIENT CATALOG NUMBER (9)
4. TITLE (and Subtitle) (6) <u>FLOATING DECK GRID MODULATOR</u>	5. TYPE OF REPORT & PERIOD COVERED First Interim Technical Report March 1977 to June 1977	
7. AUTHOR(s) (10) D. V. Savage	6. PERFORMING ORG. REPORT NUMBER	
9. PERFORMING ORGANIZATION NAME AND ADDRESS Hughes Aircraft Company Ground System Group 1901 W. Malvern, Fullerton, CA 92634	8. CONTRACT OR GRANT NUMBER(s) (15) DAAB 77-77-2-2647	
11. CONTROLLING OFFICE NAME AND ADDRESS US Army Electronics Command ATTN: DRSEL-TL-BG Fort Monmouth, NJ 07703	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS (16) 62705 1L762705 AH94 E1-01	
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office) (12) 8 p.	12. REPORT DATE (11) November 1977	
	13. NUMBER OF PAGES 15	
	15. SECURITY CLASS. (of this report) Unclassified	
16. DISTRIBUTION STATEMENT (of this Report) Approved for Public Release; Distribution Unlimited.		
17. DISTRIBUTION STATEMENT (of the abstract entered here, if different from Report)		
18. SUPPLEMENTARY NOTES		
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) TWT Grid Pulser Solid State Grid Pulser Microwave Transmitter Components		
ABSTRACT (Continue on reverse side if necessary and identify by block number) A preliminary block diagram at the modulator has been developed. The preliminary study of the 50 kV isolation pulse transformer indicates that in order to meet stability requirements, it will be necessary to clip the oscillations on the secondary and regulate the pulse top level. Three primary drive configurations are being considered.		

DD FORM 1 JAN 73 1473 EDITION OF 1 NOV 68 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

172 370

JRB

ABSTRACT

A preliminary block diagram at the modulator has been developed. The preliminary study of the 50 kV isolation pulse transformer indicates that in order to meet stability requirements, it will be necessary to clip the oscillations on the secondary and regulate the pulse top level. Three primary drive configurations are being considered.

SUMMARY

The development of a documented working model of the pulse transformer grid modulator is to be accomplished in four phases; the transformer design, the transformer driver design, the pulse top regulator design and the construction of the model. The basic configuration has been determined and the design requirements and performance characteristics defined.

PROGRAM OBJECTIVE

This program effort is intended to develop a documented working model of a pulse transformer type TWT grid modulator (See Figure 1). This particular configuration has been chosen in order to minimize the amount of circuitry at the TWT cathode potential, and thus enhances reliability and maintainability. The pulse transformer secondary will drive the TWT grid directly while referenced to the -50 kV TWT cathode potential. The primary of the transformer is to be driven by solid state circuitry operating at potentials ranging from 200 to 400 volts with respect to chassis ground. The secondary output is to be a 2 kV pulse to modulate the grid of a high powered TWT.

PROGRAM ORGANIZATION

The design portion of the program is to be accomplished in three separate phases corresponding to the three major design problems associated with a modulator of this type.

1. The transformer must be able to withstand a secondary to primary voltage stress of -50 kV and simultaneously exhibit a primary leakage inductance low enough to allow a secondary pulse rise time of 1 usec maximum.
2. The primary drive transistors must be designed to operate at very high peak power dissipations at high temperatures without failures due to secondary breakdown. The primary drive circuitry must operate with current rise and fall times $< 0.5 \mu\text{sec}$ to charge and discharge the circuit stray capacity.
3. Since the pulse transformer must be under damped to provide the short rise and fall times required, it will exhibit overshoot and ringing. The phase stability requirements of the TWT will therefore force regulation of the grid pulse top. Active circuitry must be designed to perform pulse top clipping and regulating functions and negative bias clamp functions.

BY		
DISTRIBUTION/AVAILABILITY CODES		
Dist.	Avail.	and/or SPECIAL
A		

Section ☒
Section ☐
Section ☐

Existing, proven circuit designs will be used where possible to minimize design time. The PNP transformer drive circuitry, the pulse top clipper regulator, the TWT bias fault circuitry and the TWT filament fault circuitry all as designed for the AN/TPQ-36 system can be used with very minor modifications.

FLOATING DECK FUNCTIONS

Three different devices for primary drive circuits are under investigation; the PNP transistor, the NPN transistor and the gate turn-off (GTO) SCR. Preliminary circuit designs will be used to determine the optimum performance and most economical configuration.

The pulse top clipper regulator will be in the form of a closed control loop that both clips the oscillations on the modulator transformer secondary and controls the level of the TWT grid pulse across the width of the pulse.

Since interpulse negative grid voltage must only maintain the TWT in the off state and is not otherwise critical, the bias supply may be an unregulated transformer-rectifier power supply.

The clamp supply clamps the negative overshoot from the modulator transformer to a level within the rating of the TWT.

One secondary of the power isolation transformer provides power for the TWT heater regulator. The heater regulator then provides stable power at 8V and 10A to the TWT filament. The voltage from the other secondary of the power isolation transformer is rectified and filtered and used to supply regulated 30 Vdc to 80 kHz inverters which in turn provide power to the various circuit components on the floating deck.

The TWT filament fault circuit and the TWT grid bias fault circuit provide optical signals through fiber optic couplers from the -42 kV level to transmitter control unit (TCU) interfaces at ground level. If the TWT filament voltage drifts either high or low, the "heater OK" signal to the TCU is removed and system operation is terminated. If the TWT grid bias voltage drifts above a preset value, the "bias OK" signal to the TCU is removed and system operation is terminated.

PROGRAM EXPENDITURES

Through 31 May 1977
423 hours
\$8800.00

DESIGN REQUIREMENT OUTLINE

I. DRIVERS

- a. NPN
- b. PNP
- c. GTO SCR

II. MODULATOR TRANSFORMER

- a. IN/OUT Volt Levels
- b. Driving PNT Impedance (rise time)
- c. Size, Weight

III. PULSE TOP CLIPPER

- a. Amplifier
- b. Control Element (Transistor)
- c. Voltage Shifters (Zeners)
- d. Input Circuits (Sensors)

IV. BIAS SUPPLY

- a. Bias for Mod Transformer
- b. Negative Clamp

V. INSTRUMENTATION

- a. Filament Fault
- b. Bias Fault

VI. POWER SUPPLIES

- a. TWT Heater
- b. 30 Vdc
- c. 80 kHz Inverters

MODULATOR PERFORMANCE CHARACTERISTICS

Parameter	Symbol	Design Goal
Grid pulse rise time	t_r	$< 1 \mu\text{sec}$
Grid pulse fall time	t_f	$< 1 \mu\text{sec}$
Minimum Pulse width	T_w	$1 \mu\text{sec}$
Maximum Pulse width	T_w	$10 \mu\text{sec}$
Maximum duty cycle	D_{max}	5%
Pulse top overshoot	V_{pk}	10%
Pulse top Stability	ΔE	0.0058% RMS max




Figure 1. Floating Deck Block Diagram

DISTRIBUTION LIST

Copies

12	Defense Documentation Center ATTN: DDC-TCA Cameron Station (Bldg 5) Alexandria, VA 22314
1	Code R123, Tech Library DCA Defense Comm Engrg Ctr 1860 Wiehle Ave. Reston, VA 22090
1	Defense Communications Agency Technical Library Center Code 205 (P. A. TOLOVI) Washington, DC 20305
1	Office of Naval Research Code 427 Arlington, VA 22217
1	Director Naval Research Laboratory ATTN: 2627 Washington, DC 20375
1	Commander Naval Electronics Laboratory Center ATTN: Library San Diego, CA 92152
1	CDR, Naval Surface Weapons Center White Oak Laboratory ATTN: Library, Code WX-21 Silver Spring, MD 20910
1	Rome Air Development Center ATTN: Documents Library (TILD) Griffiss AFB, NY 13441
1	Mr. Charles Cason USA Missile Command AMSMI-RHS Redstone Arsenal, AL 35809
1	Cdr, US Army Missile Command Redstone Scientific Info Center ATTN: Chief, Document Section Redstone Arsenal, AL 35809

Copies

- 1 Commander
US Army Missile Command
ATTN: DRSMI-RE (Mr. Pittman)
Redstone Arsenal, AL 35809
- 3 Commandant
US Army Aviation Center
ATTN: ATZQ-D-MA
Fort Rucker, AL 36362
- 1 Director, Ballistic Missile Defense
Advanced Technology Center
ATTN: ATC-R, PO Box 1500
Huntsville, AL 35807
- 1 Commander
US Army Intelligence Center and School
ATTN: ATSI-CD-MD
Fort Huachuca, AZ 85613
- 1 Commander
HQ Fort Huachuca
ATTN: Technical Reference Div
Fort Huachuca, AZ 85613
- 2 Commander
US Army Electronic Proving Ground
ATTN: STEEP-MT
Fort Huachuca, AZ 85613
- 1 Commander
USASA Test and Evaluation Center
ATTN: IAO-CDR-T
Fort Huachuca, AZ 85613
- 1 Deputy for Science and Technology Ofc
Assist Sec Army (R&D)
Washington, DC 20310
- 1 HQDA (DAMA-ARP/DR. F. D. Verderame)
Washington, DC 20310
- 1 Commandant
US Army Signal School
ATTN: ATSN-CTD-MS
Fort Gordon, GA 30905

Copies

- 1 Commandant
US Army Ordnance School
ATTN: ATSL-CD-OR
Aberdeen Proving Ground, MD 21005
- 1 CDR, Harry Diamond Laboratories
ATTN: Library
2800 Powder Mill Road
Adelphi, MD 20783
- 1 Director
US Army Ballistic Research Labs
ATTN: DRXBR-LB
Aberdeen Proving Ground, MD 21005
- 1 Harry Diamond Laboratories, Dept of Army
ATTN: DRXDO-RCB (DR. J. Nemarich)
2800 Powder Mill Road
Adelphi, MD 20783
- 1 Director
US Army Materiel Systems Analysis Acty
ATTN: DRXSY-T
Aberdeen Proving Ground, MD 21005
- 1 CDR, US Army Aviation Systems Command
ATTN: DRSAV-G
PO Box 209
St. Louis, MO 63166
- 1 CDR, US Army Research Office
ATTN: DRXRO-IP
PO Box 12211
Research Triangle Park, NC 07709
- 1 Commandant
US Army Inst for Military Assistance
ATTN: ATSU-CTD-MO
Fort Bragg, NC 28307
- 1 Commandant
US Army Air Defense School
ATTN: ATSA-CD-MC
Fort Bliss, TX 79916
- 1 Commander
US Army Nuclear Agency
Fort Bliss, TX 79916

Copies

- 1 Commander, HQ MASSTER
Technical Information Center
ATTN: Mrs. Ruth Reynolds
Fort Hood, TX 76544
- 1 Commander, DARCOM
ATTN: DRCDE
5001 Eisenhower Ave
Alexandria, VA 22333
- 1 CDR, US Army Security Agency
ATTN: IARDA-IT
Arlington Hall Station
Arlington, VA 22212
- 2 Commander
US Army Logistics Center
ATTN: ATCL-MC
Fort Lee, VA 22801
- 1 Chief
OFC of Missile Electronic Warfare
Electronic Warfare Lab, ECOM
White Sands Missile Range, NM 88002
- 1 Chief
Intel Materiel Dev and Support Ofc
Electronic Warfare Lab, ECOM
Fort Meade, MD 20755
- Commander
US Army Electronics Command
Fort Monmouth, NJ 07703
- 1 DRSEL-PL-ST
- 1 DRSEL-NL-D
- 1 DRSEL-WL-D
- 1 DRSEL-VL-D
- 3 DRSEL-CT-D
- 1 DRSEL-BL-D
- 1 DRSEL-TL-DT
- 3 DRSEL-TL-BG
- 1 DRSEL-TL-BG (Ofc of Record)
- 1 DRSEL-TE
- 1 DRSEL-MA-MP
- 2 DRSEL-MS-TI
- 1 DRSEL-GG-TD
- 1 DRSEL-PP-I-PI
- 1 DRSEL-GS-H

Copies

2 DRSEL-PA
1 DRSEL-RD
1 DRSEL-TL-D
1 USMC-LNO
1 TRADOC-LNO
1 DRSEL-CT-R (Mr. P. Corbert)
1 DRSEL-CT-R (Mr. R. Pearce)
1 DRCPM-FF-PA (F. Murphy)
1 DRCPM-FF-TM (R. Bertolini)
1 DRSEL-TL-IR (I. Organic)

2 MIT - Lincoln Laboratory
ATTN: Library (RM A-082)
PO Box 73
Lexington, MA 02173

1 NASA Scientific and Tech Info Facility
Baltimore/Washington INTL Airport
PO Box 8757, MD 21240

1 National Bureau of Standards
Bldg 225, Rm A-331
ATTN: Mr. Leedy
Washington, DC 20231

2 Advisory Group on Electron Devices
201 Varick Street, 9th Floor
New York, NY 10014

2 Advisory Group on Electron Devices
ATTN: Secy, Working Group D (Lasers)
201 Varick Street
New York, NY 10014

1 TACTEC
Battelle Memorial Institute
505 King Avenue
Columbus, OH 43201

1 General Electric Co., HMED
ATTN: Mr. C.J. Eichenauer, Jr.
Court Street
Syracuse, NY 13201

1 RCA - MSR Division
ATTN: Mr. Duard Pruitt
Boston Landing Road
Moorestown, NJ 08057

Copies

- 1 Dr. M. F. Rose
Naval Surface Weapons Center
White Oak Lab
Silver Spring, MD 20910
- 1 Mr. A. E. Gordon
ITT, Electron Tube Division
Box 100
Easton, PA 18042